

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Erica

Code : 0705182B

PRODUCT FAMILY

- Round applique for indoor and outdoor for wall or ceiling application (IP65)

MATERIAL CHARACTERISTICS

- Housing, diffuser-holding-ring and clip-hooks, made from stabilized, anti-UV PC (polycarbonate) coloured granules
- Opal PMMA (acrylic) diffuser
- Silicone gaskets
- A2 stainless steel screws

COLOUR

- White RAL 9003

LIGHTING CHARACTERISTICS E27

- Fluorescent light source, fixed position
- Round symmetrical light throw

WIRING CHARACTERISTICS E27

- Luminaire designed for max 15W FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz
- Max lamp dimension allowed Ø60xL140mm

WIRING CHARACTERISTICS LED

- LED's lighting source in fixed position
- Round symmetrical light throw
- Immediately ON at 100% of light flux

CARATTERISTICHE DI CABLAGGIO LED

- 11.3W LED's module with 64 LED's
- Built-in driver

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire for direct wall/ceiling fixing using n.3 screws and expansion caps (not supplied)
- Rear cable entrance through cable tray or cable entrance through external canalisation max Ø20mm
- Cable clamp for power supply cables 2x2.5mmq
- Tool-free ordinary maintenance by unhooking the n.3 clip-hooks holding diffuser for access to optic compartment

DIMENSIONS

- Ø300x100mm

TECHNICAL SPECS

- Lifetime Led's: L70/B20>54Kh - Tc85°C
- Lifetime Driver: 30Kh
- Step MacAdam: 3
- Power factor: >0.5
- Warranty: 5 years

TECHNICAL SPECS 4000K

- Led's output: 1920lm@tc25°C
- Luminaire output: 1112lm@ta25°C
- Led's consumption: 11.3W
- Luminaire consumption: 14.7W
- Led's efficiency: 164lm/W
- Luminaire efficiency: 73lm/W

TECHNICAL SPECS 3000K


- Led's output: 1856lm@tc25°C
- Luminaire output: 1075lm@ta25°C

- Led's consumption: 11.3W
- Luminaire consumption: 14.7W
- Led's efficiency: 170lm/W
- Luminaire efficiency: 76lm/W

Rev. 2 - 11/11/19

Details

- Conformity with EU Directives
- Double insulation/class II
- IK03
- RG0
- CRI>80
- IP 65



220-240V 50/60Hz 14,7W LED					
CE		IK03	RG	CRI ≥80	IP65

