

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Bambù

**Code : 1048601N**

#### PRODUCT FAMILY

- Outdoor residential round shaped complete with base for plinth/floor installation (IP55)

#### MATERIAL CHARACTERISTICS

- Housing in aluminium plated steel and integrated base in hot galvanised steel, and painted (metallic grey RAL 9006 and black textured)
- Body and integrated base in stainless steel AISI 316L
- Diffuser, flush with body in translucent UV resistant, internally prismatic PC (polycarbonate), attached to the body through a bayonet connector and sealed with a silicone gasket
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Silicone gaskets
- A2 stainless steel screws

#### COLOUR

- Metallic grey RAL 9006
- Black textured

#### LIGHTING CHARACTERISTICS

- Fluorescent light source, fixed position
- Round symmetrical light throw

#### WIRING CHARACTERISTICS

- Luminaire designed for max 21W FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz
- Max lamp dimension allowed Ø50x190mm

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire installed directly to plinth/floor with n.3 screws (not supplied) and sealed with a gasket
- Tool-free extractable gear tray from the top
- Cable clamp on gear tray, Ø5-12mm
- Terminal for cables Ø2.5mmq
- Ordinary maintenance carried out by removing diffuser by rotating and lifting, possible through bayonet connector

#### DIMENSIONS

- Ø76x660mm
- Ø76x950mm
- Ø76x1640mm
- Round shaped base Ø116

#### OPTIONAL ACCESSORIES TO BE ORDERED SEPARATELY:

- IP68 connector - COD.CS093000
- "T"-3 ways IP68 connector - COD.CS093001

- Nominal voltage: 220-240V
- Rated frequency: 50/60Hz
- Insulation Class: II
- Warranty: 5 years
- IK: 05

Rev 02-28/04/2016

#### Details

- Conformity with CEE directives
- Double insulation/class II
- IP 55



21W max E27



IP55

