

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Teo

Code : 1016101M

PRODUCT FAMILY

- Outdoor residential luminaire, suitable for upright installation on poles Ø60mm on top (IP54)

MATERIALS CHARACTERISTICS

- Housing and top cover in painted NY/FV30%
- Aluminium reflector
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Opal PMMA (acrylic) diffuser
- Silicone gaskets
- A2 stainless steel screws

COLOUR

- Anthracite RAL 7016 textured
- Metallic grey RAL 9006

LIGHTING CHARACTERISTICS

- Fluorescent light source, fixed position
- Round symmetrical light throw

WIRING CHARACTERISTICS

- Luminaire designed for max 20W FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz
- Max lamp dimension allowed Ø60xL160mm
- Terminal for power supply cables 2x2.5mmq
- Use only a flexible double insulation sheath (type HAR). The outer cable diameter must range between Ø5 and Ø12mm. The thickness of the inner electrical wires must range between 0,5 and 2,5 mmq

INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops Ø60mm, to be fixed via 2 screws
- Cable clamp for cables Ø12mm max
- Ordinary maintenance by loosening two screws and sliding the top cover

DIMENSIONS

- 311x195mm

OPTIONAL ACCESSORIES TO BE ORDERED SEPARATELY:

- IP68 connector - COD.CS093000
- "T"-3 ways IP68 connector - COD.CS093001
- Mistral metallic grey RAL 9006 - COD.1480000G
- Mistral grey RAL 9007 - COD.1480000W

RECOMMENDED POLES TO BE ORDERED SEPARATELY:

- Slick metallic grey RAL 9006 H1000 - COD.1400200G
- Slick metallic grey RAL 9006 H1500 - COD.1400300G
- Slick metallic grey RAL 9006 H2000 - COD.1400400G
- Slick grey RAL 9007 H1000 - COD.1400200W
- Slick grey RAL 9007 H1500 - COD.1400300W
- Slick grey RAL 9007 H2000 - COD.1400400W


- Nominal voltage: 220-240V
- Rated frequency: 50/60Hz
- Insulation Class: II
- Warranty: 3 years
- IK: 06

Rev 04 - 28/10/2019

Details

- Conformity with CEE directives
- Double insulation/class II
- IP 54



20W max E27		
CE		IP54

