

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Teo

Code : 1016101S

PRODUCT FAMILY

- Outdoor residential luminaire, suitable for upright installation on poles Ø60mm on top (IP54)

MATERIALS CHARACTERISTICS

- Housing and top cover in painted NY/FV30%
- Aluminium reflector
- Coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Opal PMMA (acrylic) diffuser
- Silicone gaskets
- A2 stainless steel screws

COLOUR

- Anthracite RAL 7016 textured
- Metallic grey RAL 9006

LIGHTING CHARACTERISTICS

- Light source in fixed position
- Round symmetrical light throw

WIRING CHARACTERISTICS

- Luminaire designed for max 20W LED lamp, E27 lamp holder, supply tension max 250V
- Max lamp dimension allowed Ø60xL160mm
- Terminal for power supply cables 2x2.5mmq
- Use only a flexible double insulation sheath (type HAR). The outer cable diameter must range between Ø5 and Ø12mm. The thickness of the inner electrical wires must range between 0,5 and 2,5 mmq

INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops Ø60mm, to be fixed via 2 screws
- Cable clamp for cables Ø12mm max
- Ordinary maintenance by loosening two screws and sliding the top cover
- The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm

DIMENSIONS


- 311x195mm

- Warranty: 3 years

Rev 05 17/02/2023

Details

- Conformity with EU Directives
- Double insulation/class II
- IK06
- IP 54



20W max E27



IP54

