

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Zap

**Code : 1310101M**

#### PRODUCT FAMILY

- Outdoor residential cylindrical shaped luminaire, suitable for upright installation on poles Ø60mm on top (IP65)

#### MATERIALS CHARACTERISTICS

- Base shaped like heat-sink and cone covering gear tray in NY/FV30%
- Translucent diffuser in PMMA (acrylic) with bayonet connection
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- A2 stainless steel screws

#### COLOUR

- Black
- Grey RAL 9007

#### LIGHTING CHARACTERISTICS

- Fluorescent light source, fixed position
- Round symmetrical light throw

#### WIRING CHARACTERISTICS

- Luminaire designed for max 23W FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz
- Max lamp dimension allowed Ø80xL170mm
- Terminal for power supply cables 2x2.5mmq

#### INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops or brackets Ø60mm, fixed through one dowel
- Use only a flexible double insulation sheath (type HAR). The outer cable diameter must be lower than Ø6,5mm and the thickness of the inner electrical wires must range between 0,5 and 2,5mmq
- Ordinary maintenance by removing the bayonet-connection diffuser

#### DIMENSIONS

- Ø105x300mm

#### OPTIONAL ACCESSORIES TO BE ORDERED SEPARATELY:

- IP68 connector - COD.CS093000
- "T"-3 ways IP68 connector - COD.CS093001
- Mistral - COD.1480000N
- Mistral metallic grey RAL 9006 - COD.1480000G

#### RECOMMENDED POLES TO BE ORDERED SEPARATELY:

- Slick H1000 - COD.1400200N
- Slick H1500 - COD.1400300N
- Slick H2000 - COD.1400400N
- Slick metallic grey RAL 9006 H1000 - COD.1400200G
- Slick metallic grey RAL 9006 H1500 - COD.1400300G
- Slick metallic grey RAL 9006 H2000 - COD.1400400G
- Rigo H1000 - COD.1409200N
- Rigo H1500 - COD.1409300N
- Rigo H2000 - COD.1409400N

- Nominal voltage: 220-240V
- Rated frequency: 50/60Hz
- Insulation Class: II
- Warranty: 5 years
- IK: 04

Rev 02-03/10/2017

#### Details

- Conformity with CEE directives
- Double insulation/class II
- IP 55



23W max E27



IP55

