

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l.. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Zap

Code: 1310101M

PRODUCT FAMILY

- Outdoor residential cylindrical shaped luminaire, suitable for upright installation on poles Ø60mm on top (IP65)

MATERIALS CHARACTERISTICS

- Base shaped like heat-sink and cone covering gear tray in NY/FV30%
- Translucent diffuser in PMMA (acrylic) with bayonet connection
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- A2 stainless steel screws

COLOUR

- Black
- Grey RAL 9007

LIGHTING CHARACTERISTICS

- Light source in fixed position
- Round symmetrical light throw

WIRING CHARACTERISTICS

- Luminaire designed for max 23W LED lamp, E27 lamp holder, supply tension max 250V
- Max lamp dimension allowed Ø70xL150mm
- Terminal for power supply cables 2x2.5mmq

INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops or brackets Ø60mm, fixed through one dowel
- Use only a flexible double insulation sheath (type HAR). The outer cable diameter must be lower

than \emptyset 6,5mm and the thickness of the inner electrical wires must range between 0,5 and 2.5mmg

- Ordinary maintenance by removing the bayonet-connection diffuser
- The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm

DIMENSIONS

- Ø105x300mm
- Warranty: 5 years

Rev 04 - 17/02/2023

Details

- Conformity with EU Directives
- Double insulation/class II
- IK04
- IP 55





