

47032 bertinoro (FC) Italia via s.croce, 121 (z.i.) tel. +39 0543 4687 fax +39 0543 449051

• IK08

• IP 44

info@marecoluce.it www.marecoluce.it

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l.. The company reserves the right to change models, dimensions and materials at any time without notice.

# PRODUCT DATA SHEET

# Spike Combo

# Code: 1459501B

## PRODUCT FAMILY

- Outdoor Residential for direct ground fixing, with cable and plug and complete with spherical diffuser

Ø150mm, Ø200mm , Ø250mm, Ø300mm, Ø400mm, Ø500mm (IP44)

### MATERIALS CHARACTERISTICS

- Housing in NY/FV30%, black colour
- Spherical diffuser in white opal PMMA (acrylic) Ø150mm, Ø200mm, Ø250mm, Ø300mm,
- Ø400mm, or Ø500mm
- A2 stainless steel screws

#### COLOR

- Black/white opal

#### LIGHTING CHARACTERISTICS

- Light source in fixed position
- Round symmetrical light throw

#### WIRING CHARACTERISTICS

- Luminaire designed for max 8W LED lamp, E27 lamp holder, supply tension max 250V (diffuser Ø150mm)

- Max lamp dimension allowed Ø70xL110mm (diffuser Ø150mm)
- Luminaire designed for max 11W LED lamp, E27 lamp holder, supply tension max 250V (diffuser  $\emptyset$ 200mm)
- Max lamp dimension allowed Ø70xL130mm (diffuser Ø200mm)

- Luminaire designed for max 20W LED lamp, E27 lamp holder, supply tension max 250V (diffuser  $\emptyset$ 250mm)

- Max lamp dimension allowed Ø85xL170mm (diffuser Ø250mm)

- Luminaire designed for max 21W LED lamp, E27 lamp holder, supply tension max 250V (diffuser Ø300mm)

- Max lamp dimension allowed Ø100xL190mm (diffuser Ø300mm)

- Luminaire designed for max 27W LED lamp, E27 lamp holder, supply tension max 250V (diffuser Ø400mm)

- Max lamp dimension allowed Ø100xL190mm (diffuser Ø400mm)

- Luminaire designed for max 33W LED lamp, E27 lamp holder, supply tension max 250V (diffuser Ø500mm)

- Max lamp dimension allowed Ø100xL210mm (diffuser Ø500mm)
- PG9 plastic cable glande
- 2x1mmq H05RN-F cable 2,5mts long with two pins plug (supplied)

INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Screw-shaped housing for direct ground fixing
- Ordinary maintenance by removing the bayonet-connection diffuser

#### DIMENSIONS

- Ø150x428mm
- Ø200x476mm
- Ø250x517mm
- Ø300x578mm
- Ø400x675mm
- Ø500x775mm

• Warranty: 2 years

Rev 02 -20/02/2023

Details

Conformity with EU Directives

Double insulation/class II







