
47032 bertinoro (FC) Italia
via s.croce, 121 (z.i.)
tel. +39 0543 4687
fax +39 0543 449051
info@marecoluce.it
www.marecoluce.it

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET
Diffuser Ø400/500 PMMA
Code : 2060600T



PRODUCT FAMILY
- Spherical diffuser for use on thermoplastic wired bases (IP65) Ø400mm, Ø500mm, Ø600mm

MATERIAL CHARACTERISTICS
- Diffuser in spherical shape with bayonet neck Ø400mm, Ø500mm, Ø600mm
- PMMA (acrylic): for an excellent light transmission, and resistance to the most difficult weather conditions, and polluting agents. UV ray resistant.
- Semi-covered diffuser: spherical diffuser in PMMA (acrylic) Ø400mm, Ø500mm transparent, upper half
painted (uplight assembly) or lower half painted (downlight assembly) internally with reflective aluminium,
and externally with opaque black paint

LIGHTING CHARACTERISTICS
- The spherical half-painted diffusers help to direct the light beam down. By using a reflector (louvre) the
efficiency performance of the light fitting increases significantly, and an unnecessary dispersion of light
is avoided
- Having the same amount of light on the floor, it is possible to save up to the 40% of energy

INSTALLATION CHARACTERISTICS
- For use on thermoplastic wired bases, and with accessories Quasar, Sun, Giubar

COLOUR
- White
- Transparent
- Smoked
- Semi-covered

Rev 03-19/10/2020

Details
• IK08
• IP

