

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Lira 140 Led Round

**Code : 4140582W**

#### PRODUCT FAMILY

IP67 Inground/ wall Uplight or false ceiling Downlight.

#### MATERIAL CHARACTERISTICS

Body in anodised, die-cast aluminium alloy EN AB 46100

Ring in S.Steel AISI 316L with 2.5mm thickness and micro-shot blasted

Diffuser in flat, tempered glass, and with a thickness of 8mm

Colour: S.Steel

Gaskets in silicone

Screws in stainless steel A2

#### LIGHTING CHARACTERISTICS

• Vossloh-Schwabe LED Module - Direct supply tension LED versions

##### LED Output

8W - 4000K 688 lm

8W - 3000K 656 lm

##### LED luminaire output

8W - 4000K 384 lm

8W - 3000K 366 lm

Step MacAdam 3

Cable included 3x1mmq H05RNF (0.4mt)

##### Flood beam optics

• Citizen LED Module 700mA supply version (electronic driver not included)

##### LED output

6.8W - 4000K 834 lm

6.8W - 3000K 809 lm

##### LED luminaire output

6.8W - 4000K 619 lm

6.8W - 3000K 600 lm

Step MacAdam 3

Adjustable optics  $\pm 15^\circ$

Darkoo lenses

$8^\circ 20^\circ$

Cable included 2x1mmq H05RNF (0.4mt)

• Version GU10 lamp holder

Adjustable optics  $\pm 15^\circ$

Direct supply tension 220-240V 50/60Hz

Cable included 3x1mmq H05RNF (0.4mt)

#### WIRING CHARACTERISTICS

Factory-sealed termination chamber – utilising resin to guarantee sealing

Metal PG9 cable gland

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Ceiling downlight for direct mounting, requiring  $\varnothing 126\text{mm}$  hole with locking mechanism (supplied separately)

- Inground/wall light for use with recessed box accessory (supplied separately)

Ordinary maintenance (usually unnecessary for LED products) by removing the n.4 screws from ring and removing diffuser

#### MEASUREMENT CHARACTERISTICS

Ring  $\varnothing 140\text{mm}$  (with 2.5mm height)

Depth 122.5mm

Maximum drive-over load: 2500Kg at 20Km/h

#### ACCESSORIES

- Compulsory for pavement mounting

Recessed box (code: 7000.0005)

- Compulsory for false ceiling mounting

locking mechanism kit (code. 4000000W)

Optional:

Electronic driver 700mA 33W (Cod. CS160020)

IP68 connector (Cod. CS093000)

"T"-3 way IP68 connector (Cod. CS093001)

#### Details

- Conformity with CEE directives
- Energy-saving fittings
- Electronic supply
- Resistant to atmospheric agents
- Inalterable to ultraviolet radiations
- Ground recessed
- Ceiling recessed
- Drive over
- IP 67

