

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Tetris 1

Code : 1260192S

#### PRODUCT FAMILY

- Outdoor residential square shaped complete with base for plinth/floor installation (IP65)

#### MATERIALS CHARACTERISTICS

- Top cover and base made of die-cast aluminium (ADC12) anodized and painted
- Housing made of extruded aluminium EN AW 6060 with thermal treatment, subjected to cleaning and degreasing treatment before anodizing and painting
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Painted diffuser frame in NY/FV30%
- Diffuser in thick transparent PMMA (acrylic)
- Silicone gaskets
- Anti-vandal A2 stainless steel screws

#### COLOUR

- Black textured

#### LIGHTING CHARACTERISTICS

- Mains powered LED's lighting source in fixed position (17W)
- LED's lighting source in fixed position (7.7W, 15.6W, 30.1W)
- Immediately ON at 100% of light flux
- Monochromatic LED module
- Led's 1x17W EA Ø100 (4 lights)
- Led's Vossloh DLM028C40GR with 1, 2 or 3 Led's (1,2 o 4 lights)

#### WIRING CHARACTERISTICS LED

- 17W LED's module supply tension 220-240V 50/60Hz
- LED's module 6.6W, 13.2W e 26.4W
- Built-in driver (1050mA driver output)
- External cable and IP68 terminal block supplied (housed inside fitting)
- Use only a flexible supply cable in double sheath type HAR, with external diameter between Ø5 and Ø13mm, and section of the internal conductors between 0.5 and 1.5mmq

#### INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire installed directly to plinth/floor to be fixed to a counter flange with n.4 screws (not supplied)
- Ordinary and extraordinary maintenance not necessary

#### DIMENSIONS

- 200x200x600mm
- 200x200x1000mm

#### OPTIONAL ACCESSORIES (TO BE ORDERED SEPARATELY):

- Cod. CS093001 "T"-3 ways IP68 connector
- Cod. 4000.005W Anchor bolts kit (n°4 anchor bolts + n°4 nut + n°4 washers) M12x200mm made of hot-dip galvanised steel 75m UNI EN 1461

#### TECHNICAL SPECS

- Step MacAdam: 3
- Warranty: 3 years

#### TECHNICAL SPECS 4000K - 17W (4 lights)

- Led's output: 1700lm@tc25°C
- Luminaire output: 422lm@ta25°C
- Led's efficiency: 100lm/W
- Luminaire efficiency: 25lm/W
- Led's consumption: 17W
- Luminaire consumption: 17W
- Type of Led's: EA Ø100

- Lifetime Led's: L70 B50=56Kh@85°C

#### TECHNICAL SPECS 4000K - 7.7W (1 light)

- Led's output: 875lm@tc25°C
- Luminaire output: 754lm@ta25°C
- Led's efficiency: 133lm/W
- Luminaire efficiency: 114lm/W
- Led's consumption: 6.6W
- Luminaire consumption: 7.7W
- Type of Led's: Vossloh DLM028C40GR
- Lifetime Led's:  
L90/B10=32kh@65°C  
L80/B10=48kh@65°C  
L70/B10=64kh@65°C
- Power factor: >0.91

#### TECHNICAL SPECS 4000K - 15.6W (2 lights)

- Led's output: 1749lm@tc25°C
- Luminaire output: 1508lm@ta25°C
- Led's efficiency: 133lm/W
- Luminaire efficiency: 114lm/W
- Led's consumption: 13.2W
- Luminaire consumption: 15.6W
- Type of Led's: Vossloh DLM028C40GR
- Lifetime Led's:  
L90/B10=32kh@65°C  
L80/B10=48kh@65°C  
L70/B10=64kh@65°C
- Power factor: >0.5


#### TECHNICAL SPECS 4000K - 30.1W (4 lights)

- Led's output: 3498lm@tc25°C
- Luminaire output: 3016lm@ta25°C
- Led's efficiency: 133lm/W
- Luminaire efficiency: 114lm/W
- Led's consumption: 26.4W
- Luminaire consumption: 30.1W
- Type of Led's: Vossloh DLM028C40GR
- Lifetime Led's:  
L90/B10=32kh@65°C  
L80/B10=48kh@65°C  
L70/B10=64kh@65°C
- Power factor: >0.9

Rev 03-04/12/2019

#### Details

- Conformity with CEE directives
- Double insulation/class II
- IK08
- RG1
- CRI>80
- CLASS A+
- IP 65



220-240V 50/60Hz 17W

CE IK08 RG CRI ≥80 A+ IP65

