
47032 bertinoro (FC) Italia
via s.croce, 121 (z.i.)
tel. +39 0543 4687
fax +39 0543 449051
info@marecoluce.it
www.marecoluce.it

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

# PRODUCT DATA SHEET

## Tower

## Code : 1302201F




| 21W max E27 | | | |
|---|---|---|---|
| CE | ⧈ | IK 08 | IP44 |

PRODUCT FAMILY
- Outdoor Residential for direct installation on boundary walls/floor, complete with spherical diffuser Ø150mm, Ø200mm, Ø250mm (IP44)

MATERIALS CHARACTERISTICS
- Housing in NY/FV30%, black colour
- Spherical diffuser in white opal PMMA (acrylic) Ø150mm, Ø200mm or Ø250mm
- A2 stainless steel screws

COLOR
- Black/white opal

LIGHTING CHARACTERISTICS
- Liight source in fixed position
- Round symmetrical light throw

WIRING CHARACTERISTICS
- Luminaire designed for max 8W LED lamp, E27 lamp holder, supply tension max 250V (diffuser Ø150mm)
- Max lamp dimension allowed Ø70xL110mm (diffuser Ø150mm)
- Luminaire designed for max 11W LED lamp, E27 lamp holder, supply tension max 250V (diffuser Ø200mm)
- Max lamp dimension allowed Ø70xL160mm (diffuser Ø200mm)
- Luminaire designed for max 20W LED lamp, E27 lamp holder, supply tension max 250V (diffuser Ø250mm)
- Max lamp dimension allowed Ø85xL180mm (diffuser Ø250mm)

INSTALLATION AND MAINTENANCE CHARACTERISTICS
- Luminaire for installation on boundary walls/floor, fixed with 2 screws (not supplied)
- Ordinary maintenance by removing the bayonet-connection diffuser

DIMENSIONS
- Ø150x300mm
- Ø200x324mm
- Ø250x374mm

• Warranty: 2 years

Rev 02 - 20/02/2023

Details
• Conformity with EU Directives
• Double insulation/class II
• IK08
• IP 44

