

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Wix Led

Code : 1056192M

PRODUCT FAMILY

- Outdoor residential round shaped complete with base for plinth/floor installation (IP55)

MATERIAL CHARACTERISTICS

- Top cover and base made of die-cast aluminium (ADC12) anodized and painted
- Housing made of extruded aluminium EN AW 6060 with thermal treatment, subjected to cleaning and degreasing treatment before anodizing and painting
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- Diffuser in thick transparent PMMA (acrylic) or PC (polycarbonate)
- PC (polycarbonate) diffuser cone, moulded white
- Silicone gaskets
- A2 stainless steel screws

COLOUR

- Black textured
- Metallic grey RAL 9006
- White RAL 9003

LIGHTING CHARACTERISTICS

- Mains powered LED's lighting source in fixed position
- Immediately ON at 100% of light flux
- Round symmetrical light throw
- Monochromatic LED module
- Led's 1x17W EA Ø100

WIRING CHARACTERISTICS

- 17W LED's module supply tension 220-240V 50/60Hz
- External cable and IP68 terminal block supplied (housed inside fitting)
- Use only a flexible supply cable in double sheath type HAR, with external diameter between Ø7 and Ø12mm, and section of the internal conductors between 0.5 and 1.5mmq

INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire installed directly to plinth/floor with n.3 screws (not supplied)
- Ordinary and extraordinary maintenance not necessary

DIMENSIONS

- Ø200x1000mm
- Round shaped base Ø254

OPTIONAL ACCESSORY TO BE ORDERED SEPARATELY:

- "T"-3 ways IP68 connector - COD.CS093001


TECHNICAL SPECS 3000K/4000K

- Led's output: 1700lm@tc25°C
- Luminaire output: 1358lm@ta25°C
- Led's efficiency: 100lm/W
- Luminaire efficiency: 80lm/W
- Led's consumption: 17W
- Luminaire consumption: 17W
- Tipo LED's: EA Ø100
- Lifetime Led's: L70 B50=56Kh@85°C
- Step MacAdam: 3
- Warranty: 3 years
- IK: 04 (PMMA)
- IK: 08 (PC)

Rev 02-29/10/2019

Details

- Conformity with CEE directives
- Double insulation/class II
- IK04
- IK08
- RG1
- CRI>80
- CLASS A+
- IP 55



220-240V 50/60Hz 17W
 CE □ IK04 IK08 RG1 CRI>80 A+ IP55

