

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Smart

Code : 0251184B

PRODUCT FAMILY

- Led round applique for indoor and outdoor for wall or ceiling application (IP65) through the Click fastening system

MATERIAL CHARACTERISTICS

- Housing (base) and deflector made from stabilized, anti-UV ABS-coloured granules (white colour)
 - Diffuser in opal PMMA (acrylic) sealed with pure neutral silicone, anti-mold with low elastic modulus
 for an excellent resistance to aging, weathering, and UV rays (only LED version 15W)
 - A2 stainless steel screws

Mechanical properties of silicone, polymerized 7 days at 22°C and 50% relative humidity

- Hardness, Shore A 37
 - Tensile strength MPa 2,5
 - Elongation at break %680

COLOUR

- White RAL 9003

LIGHTING CHARACTERISTICS

- LED lighting source mains supplied, in a fixed position
 - Round symmetrical light throw
 - Immediately ON at 100% of the light flux

WIRING CHARACTERISTICS

- LED's module 10W mains powered 220-240V 50/60Hz
 - Monochromatic LED's module (80 LED's)
 - LED's HONGLITRONIC® 2835 with beam 120°

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire for direct wall/ceiling fixing through Click fastening system

COMPULSORY ACCESSORY - COD.4000.1000

- Click: Reinforced thermoplastic patented fastening system for ceiling lamps of the Click and Light range

DIMENSIONS

- Ø250x90mm

TECHNICAL SPECS 3000K/4000K


- LED's output: 1000lm@ta25°C
- Luminaire output: 688lm@ta25°C
- LED's efficiency: 100lm/W
- Luminaire efficiency: 69lm/W
- LED's consumption: 10W
- Luminaire consumption: 10W
- LED's type: Hongli 2835DW
- Step MacAdam: 3
- Lifetime Led's: L70>54Klh - Tc85°C
- Nominal voltage: 220-240V
- Nominal frequencies: 50/60Hz
- Insulation class: II
- RG: 0
- CRI: >80
- Warranty: 5 years
- IK: 03

Rev. 2 - 08/11/19

Details

- Conformity with CEE directives
- Double insulation/class II
- IP 65



220-240V 50/60Hz 10W		
CE		IP65

