

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Smart

**Code : 0251182B**

#### PRODUCT FAMILY

- Led round applique for indoor and outdoor for wall or ceiling application (IP65) through the Click fastening system

#### MATERIAL CHARACTERISTICS

- Housing (base) and deflector made from stabilized, anti-UV ABS-coloured granules (white colour)  
 - Diffuser in opal PMMA (acrylic) sealed with pure neutral silicone, anti-mold with low elastic modulus for an excellent resistance to aging, weathering, and UV rays (only LED version 15W)  
 - A2 stainless steel screws

Mechanical properties of silicone, polymerized 7 days at 22°C and 50% relative humidity

- Hardness, Shore A 37  
 - Tensile strength MPa 2,5  
 - Elongation at break %680

#### COLOUR

- White RAL 9003

#### LIGHTING CHARACTERISTICS

- LED lighting source mains supplied, in a fixed position  
 - Round symmetrical light throw  
 - Immediately ON at 100% of the light flux

#### WIRING CHARACTERISTICS

- LED's module 10W mains powered 220-240V 50/60Hz  
 - Monochromatic LED's module (80 LED's)

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire for direct wall/ceiling fixing through Click fastening system

#### COMPULSORY ACCESSORY - COD.4000.1000

- Click: Reinforced thermoplastic patented fastening system for ceiling lamps of the Click and Light range

#### DIMENSIONS

- Ø250x90mm


#### TECHNICAL SPECS 3000K/4000K

- LED's output: 1000lm@ta25°C
- Luminaire output: 688lm@ta25°C
- LED's efficiency: 100lm/W
- Luminaire efficiency: 69lm/W
- LED's consumption: 10W
- Luminaire consumption: 10W
- Step MacAdam: 3
- Lifetime Led's: L70>54Khr - Tc85°C
- Warranty: 5 years

Rev. 2 - 08/11/19

#### Details

- Conformity with CEE directives
- Double insulation/class II
- IK03
- RG0
- CRI>80
- IP 65



220-240V 50/60Hz 10W					
CE		IK03	RG0	CRI ≥80	IP65

