

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

New Stelo TP

Code : 1053101N

PRODUCT FAMILY

- Outdoor residential cylindrical shaped luminaire, suitable for upright installation on poles Ø60mm on top (IP65)

MATERIALS CHARACTERISTICS

- Screw-neck diffuser in translucent PMMA (acrylic) with brushed effect, connected to the lamp-holder compartment via a black polycarbonate joint, and sealed with pure neutral silicone anti-mold with low elastic modulus for an excellent resistance to aging, weathering, and UV rays
- Lamp holder compartment in black PC (polycarbonate)
- Fixing spring in harmonic steel AISI 301
- Silicone gaskets
- A2 stainless steel screws

Mechanical properties of silicone, polymerized 7 days at 22°C and 50% relative humidity

- Hardness, Shore A 37
- Tensile strength MPa 2,5
- Elongation at break %680

COLOUR

- Black

WEIGHT

- Luminaire: 0.300kg
- Single package: 0.480kg (373x105x105mm)

LIGHTING CHARACTERISTICS

- Fluorescent light source, fixed position
- Round symmetrical light throw

WIRING CHARACTERISTICS

- Luminaire designed for max 11W FBT lamp E27 lamp holder supply tension 220-240V 50-60Hz
- Max lamp dimension allowed Ø60xL115mm
- PG9 plastic cable gland equipped with osmotic valve for air and humidity leakage (reducing the overpressures)
- Connection to the main supply through a H05RN-F 2x0.75sqmm pre-wired cable (50cm) out of the luminaire

INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops or brackets Ø60mm with maximum thickness 3mm
- Fixing by harmonic steel springs
- Ordinary maintenance by untightening the diffuser with screw base
- The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm

DIMENSIONS

- Round shaped diffuser Ø80mm once installed on the pole. Visible part Ø80x165mm
- Total height 278mm

OPTIONAL ACCESSORIES TO BE ORDERED SEPARATELY:

- IP68 connector - COD.CS093000
- "T"-3 ways IP68 connector - COD.CS093001
- Mistral - COD.1480000N

RECOMMENDED POLES TO BE ORDERED SEPARATELY:

- Slick H1000 - COD.1400200N
- Slick H1500 - COD.1400300N
- Slick H2000 - COD.1400400N
- Full black H1000 - COD.1403200N
- Full black H1500 - COD.1403300N
- Full black H2000 - COD.1403400N


- Rigo H1000 - COD.1409200N
- Rigo H1500 - COD.1409300N
- Rigo H2000 - COD.1409400N

- Warranty: 5 years

Rev 01-05/07/2018

Details

- Conformity with CEE directives
- Double insulation/class II
- IK02
- IP 65



220-240V 50/60Hz 11W max E27

