

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Lynx 60x60 UGR19 1-10V

Code : 0401882G

#### PRODUCT FAMILY

- Square LED panel 60x60 (IP40) flicker free and UGR <19 for ceiling, recessed, or suspension mounting through the relevant accessories (to be ordered separately)

#### MATERIAL CHARACTERISTICS

- Extruded aluminium housing, anodized and white coated
- Opal PC (polycarbonate) diffuser, for a very good light transmittance and uniformity
- Transparent PMMA (acrylic) LGP thickness 2mm
- Safety kit (safety cable) in galvanised steel
- Polyester powder coating
- A2 stainless steel screws

#### COLOR

- White

#### WEIGHT

- LED panel: 3,2Kg
- Single package: 3,8Kg (615x40xh670mm)
- Multiple package with 4pcs: 16,6Kg (640x200x700mm)
- Multiple package with 6pcs: 21,2Kg (650x175x685mm)

#### LIGHTING CHARACTERISTICS

- Lighting source in a fixed position
- Immediately ON at 100% of the light flux

#### WIRING CHARACTERISTICS

- External 1-10V driver 200-240V 50/60Hz (included), to be connected to the LED panel via quick-connector (included)
- N° 192 Led's smd 4014 (40W)
- N° 216 Led's smd 4014 (45W)
- Driver output 1000mA (40W) with TUV certification IP20 flicker free
- Driver output 1100mA (45W) with ENEC 25/TUV certification IP20 flicker free

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Direct installation in false ceiling in replacement of standard panels 600x600mm
- Installation on drywall with the use of fixing clips (to be ordered separately), by making a square hole 570x570mm
- Suspended installation by using 4 anchors (to be ordered separately)
- Ceiling installation by using a frame (to be ordered separately)
- Safety kit (safety cable) included
- Ordinary maintenance not necessary

#### DIMENSIONS

- 595x595x10.5mm

#### OPTIONAL ACCESSORIES (TO BE ORDERED SEPARATELY)

- Code 0400.000B Frame 600x600mm for ceiling installation
- Code 0400.0002 Suspension (4 anchors)
- Code 0400.0004 Fixing Clips for false ceiling installation (4 clips)

#### TECHNICAL SPECS

- Led's: SMD 4014
- Step MacAdam: 3
- Lifetime Led: 50Kh
- Lifetime driver: 50Kh
- Power factor: 0.98
- UGR: <19
- Warranty: 5 years

#### TECHNICAL SPECS 4000K - 40W

- Luminaire output: 4014lm@ta25°C
- Led's consumption: 34W
- Luminaire consumption: 40W
- Led's efficiency: 100lm/W

#### TECHNICAL SPECS 3000K - 40W

- Luminaire output: 3800lm@ta25°C
- Led's consumption: 34W
- Luminaire consumption: 40W
- Led's efficiency: 95lm/W

#### TECHNICAL SPECS 4000K - 45W

- Luminaire output: 4577lm@ta25°C
- Led's consumption: 38.3W
- Luminaire consumption: 45W
- Led's efficiency: 102lm/W


#### TECHNICAL SPECS 3000K - 45W

- Luminaire output: 4250lm@ta25°C
- Led's consumption: 38.3W
- Luminaire consumption: 45W
- Led's efficiency: 94lm/W

Rev. 5 - 06/07/20

#### Details

- Conformity with CEE directives
- Double insulation/class II
- IK07
- RG0
- CRI>80
- CLASS A+
- Dimmable
- IP 40



200-240V 50/60Hz 45W

