

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Hydra 19,2W/m

Code : 05536882

PRODUCT FAMILY

- High efficiency LED strip with adhesive film, for indoor use (IP20)
- High efficiency LED strip with adhesive film, for outdoor/indoor use (IP65/68)

MATERIAL CHARACTERISTICS

- Flexible PCB with expanded copper tracks (0,1mm thick) with 3M LSE300 adhesive film (IP20/65/68)
- Led chip protected by a polyurethane glue coating to ensure high resistance to low temperatures and yellowing (IP65)
- LED chip protected by a polyurethane glue coating and silicone sheath to ensure high resistance to low temperatures and yellowing (IP68)

WEIGHT

strip led:

- 90g/5m (IP20)
- 200g/5m (IP65)
- 340g/5m (IP65)

single package:

- 128g (190x200x18mm) (IP20)
- 224g (190x200x18mm) (IP65)
- 365g (190x200x18mm) (IP68)

LIGHTING CHARACTERISTICS

- LED's with a frontal light throw, beam 120°
- 120 LED's/m
- Anti-static packaging
- 3 ounces copper thickness
- Led's 2835

WIRING CHARACTERISTICS

- Driver connection simplified via a pre-wired cable complete with watertight connector IP65 and IP68 (included).
- The strip can be cut in units of 5cm by using scissors
- Maximum length 8m, with low luminous decay and high uniformity

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- The strip must be installed on a heat sink (aluminium profile or equivalent)
- Installation can be carried out by using the 3M LSE300 thermal conductive tape on rigid profiles, available as accessories for exposed installation
- Ordinary maintenance not necessary

DIMENSIONS

- 10x3mm in reels of 5m (IP20)
- 10x4mm in reels of 5m (IP65)
- 12x6mm in reels of 5m (IP68)

TECHNICAL SPECS

- Luminaire consumption: 19,2W/m
- Maximum length: 8m
- Chip Led's: 2835
- Number of LED's/m: 120
- Step McAdam: 3
- Lifetime Led: 30Kh

TECHNICAL SPECS 4000K - IP20

- LED's output: 1824lm@tc25°C
- Luminaire output: 1824lm@ta25°C
- Luminous efficacy: 95lm/W

TECHNICAL SPECS 3000K - IP20

- LED's output: 1785lm@tc25°C
- Luminaire output: 1785lm@ta25°C
- Luminous efficacy: 93lm/W

TECHNICAL SPECS 4000K - IP65

- LED's output: 1824lm@tc25°C
- Luminaire output: 1805lm@ta25°C
- Luminous efficacy: 94lm/W

TECHNICAL SPECS 3000K - IP65

- LED's output: 1785lm@tc25°C
- Luminaire output: 1776lm@ta25°C
- Luminous efficacy: 93lm/W

TECHNICAL SPECS 4000K - IP68

- LED's output: 1824lm@tc25°C
- Luminaire output: 1785lm@ta25°C
- Luminous efficacy: 93lm/W


TECHNICAL SPECS 3000K - IP68

- LED's output: 1785lm@tc25°C
- Luminaire output: 1756lm@ta25°C
- Luminous efficacy: 92lm/W

Rev. 1 - 12/09/19

Details

- Conformity with EU Directives
- Class III
- RG0
- CRI>80
- IP



24VDC 19,2W/mt

