

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Bellatrix

Code : 0724182B

PRODUCT FAMILY

- LED round surface applique for wall and ceiling mounting, indoor and outdoor use (IP65)

MATERIAL CHARACTERISTICS

- Housing in white PC (polycarbonate)
- Frame in white PC (polycarbonate)
- Diffuser in PC (polycarbonate) sealed to the base with pure neutral silicone glue, anti-mold with low elastic modulus for an excellent resistance to aging, weathering, and UV rays, to ensure the IP65 rate
- Galvanized sheet bracket for wall/ceiling fixing
- A2 stainless steel screw

COLOR

- White RAL 9003

WEIGHT

- 370gr

LIGHTING CHARACTERISTICS

- Lighting source is in a fixed position
- Round symmetrical light throw
- LED circuit with self-dissipating PCB in IMS
- Immediately ON at 100% of light flux

WIRING CHARACTERISTICS

- 18W LED's module secured on the base of the luminaire supply tension 220-240V 50-60Hz
- Simplified connection via bipolar terminal in water-tight compartment
- Built-in driver

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Light fixture for direct wall/ceiling application to be installed through a metal bracket (included)
- Power supply cable entry through a cable gland
- For the electrical connection, use a double insulation cable Ø3-7mm
- Housing to be secured to the installation surface by 2 dowels (not included)
- The diffuser is glued to the base
- Ordinary maintenance not necessary

DIMENSIONS

- Ø221x72mm

TECHNICAL SPECS

- Step MacAdam: 2
- Power factor: >0,9
- Lifetime Led's: 30Kh
- Lifetime Driver: 30Kh
- Garanzia: 3 years

TECHNICAL SPECS 4000K

- LED's output: 2080lm@tc25°C
- Luminaire output: 1600lm@ta25°C
- LED's consumption: 18W
- Luminaire consumption: 20W


TECHNICAL SPECS 3000K

- LED's output: 1950lm@tc25°C
- Luminaire output: 1500lm@ta25°C
- LED's consumption: 18W
- Luminaire consumption: 20W

Rev. 02 - 27/02/2023

Details

- Conformity with EU Directives
- Double insulation/class II
- IK08
- RG0
- CRI>80
- IP 65



220-240V 50/60Hz 20W					
CE	□	IK08	RG	CRI ≥80	IP65

