

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Driver IP20 75W-24V

**Code : 05992002**

#### PRODUCT FAMILY

- Elettronic driver

#### OUTPUT

- DC voltage: 24V
- Rated current: 3.2A
- Current range: 0~3.2A
- Rated power: 76.8W
- Ripple & noise (max.): 150mVp-p
- Voltage ADJ. range: 21.6~28.8V
- Setup, rise time: 500ms, 30ms/230VAC - 500ms ,30ms/115VAC at full load
- Hold up time: 60ms/230VAC; 12ms/115VAC at full load

#### INPUT

- Voltage range: 85~264VAC/120~373VDC
- Frequency range: 47~63Hz
- AC current: 1.4A/115VAC - 0.85A/230VAC
- Inrush current: cold start 65A/230VAC
- Leakage current: <0.75mA/240VAC

#### PROTECTION

- Over load: 110~150% rated output power
- Protection type : Hiccup mode, recovers automatically after fault condition is removed
- Over voltage: 28.8~33.6V

#### ENVIRONMENT

- Working temp.: -30~+70°C
- Compliance to IECIEN 60335-1(PD3) and IEC1EN61558-1, -2-16

Rev. 1 - 18/9/19

#### Details

- Conformity with EU Directives
- IP 20



CE	IP20