

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Edge wall 60°

Code : 0173182J

PRODUCT FAMILY

- Outdoor residential Led rectangular shaped 125x90mm complete with fixing bracket for wall mounting (IP65)

MATERIAL CHARACTERISTICS

- Housing made of extruded aluminium EN AW 6060 with thermal treatment, subjected to cleaning and degreasing treatment before anodizing and painting
 - Interlocking decorative side profile in PC (polycarbonate)
 - Reinforced thermoplastic and painted front closure cap
 - 94x30x25mm wall fixing bracket made of cold-dip galvanized steel 75m UNI EN 1461
 - Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
 - Screws in stainless steel A2

COLOR

- Metallic grey RAL 9006
 - Anthracite RAL 7016 textured
 - Rust

LIGHTING CHARACTERISTICS

- LED's lighting source in fixed position
 - Immediately ON at 100% of light flux
 - Pedestrian LED optics in PMMA (acrylic) with high performances
 - Monochromatic LED module (12 Led's)
 - LED's Seoul smd 3030
 - PCB in IMS thickness 1,6mm

WIRING CHARACTERISTICS

- LED's module 9.3W
 - Built-in driver IP67 (500mA driver output)
 - LED circuit secured on the aluminium housing/heat-sink
 - IP68 terminal block included
 - Use only a flexible supply cable in double sheath type HAR, with external diameter between Ø7 and Ø12mm, and section of the internal conductors between 0.5 and 1.5mmq

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire for direct wall mounting to be installed through expansion caps (not supplied)
 - Ordinary and extraordinary maintenance not necessary

DIMENSIONS

- 235x125x90mm

OPTIONAL ACCESSORY TO BE ORDERED SEPARATELY:

- "T"-3 ways IP68 connector - COD.CS093001

TECHNICAL SPECS

- Led's consumption: 9.3W
- Luminaire consumption: 10.9W
- Type of Led's: Seoul smd 3030
- Step MacAdam: 3
- Lifetime Led's: L90/B50>54Kh - Tc 105°C
- Warranty: 3 years

TECHNICAL SPECS 4000K

- Led's output: 1351lm@tc25°C
- Luminaire output: 1220lm@ta25°C
- Led's efficiency: 145lm/W
- Luminaire efficiency: 112lm/W


TECHNICAL SPECS 3000K

- Led's output: 1260lm@tc25°C
- Luminaire output: 1137lm@ta25°C
- Led's efficiency: 135lm/W
- Luminaire efficiency: 104lm/W

Rev. 1 - 06/03/20

Details

- Conformity with CEE directives
- Double insulation/class II
- IK08
- RG1
- CRI>80
- CLASS A+
- IP 65



90-264V 50/60Hz 10,9W						
CE	□	IK 08	RG 1	CRI ≥80	A+	IP65

