

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Edge pole top

**Code : 0170182S**

#### PRODUCT FAMILY

- Urban architectural CUT-OFF LED rectangular shaped 125x90mm for pole top use on Ø60mm poles (IP65)

#### MATERIAL CHARACTERISTICS

- Housing made of extruded aluminium EN AW 6060 with thermal treatment, subjected to cleaning and degreasing treatment before anodizing and painting
- Interlocking decorative side profile in PC (polycarbonate)
- Reinforced thermoplastic and painted front closure cap
- Round pole top in hot-dipped galvanized steel S235JR UNI EN 10219, 75µm thick UNI EN 1461
- Polyester powder coating with a pretreatment (Phosphochromating method) to ensure high protection against weathering
- A2 stainless steel screws

#### COLOUR

- Anthracite RAL 7016 textured

#### LIGHTING CHARACTERISTICS

- LED's lighting source in fixed position
- Monochromatic LED module (12 Led's - 25,2W) powered at 350mA
- Monochromatic LED module (12 Led's - 50,7W) powered at 700mA
- Street medium LED optics in PMMA (acrylic) with high performances
- Non yellowing, transparent PMMA (acrylic) lens
- Immediately ON at 100% of the light flux
- CUT-OFF light fitting conforming to all regional/local laws against light pollution

#### WIRING CHARACTERISTICS

- LED circuit secured on the aluminium housing/heat-sink
- Driver IP67 included (DALI dimmable version available on request)

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on Ø60mm poles
- Pre-wired with H07RN-F 2x1.5mmq cable (70cm) for the connection to the mains
- Ordinary and extraordinary maintenance (not necessary)

#### DIMENSIONS

- 125x90x500mm

#### TECHNICAL SPECS

- Step MacAdam: 3
- Lifetime LED's:  
L85/B50>60Kh - Tc 70°C-105°C  
L90/B50>50Kh - Tc 70°C
- Warranty: 3 years

#### TECHNICAL SPECS 4000K - 28,7W

- LED's output: 4032lm@tc25°C
- Luminaire output: 3600lm@ta25°C
- LED's efficiency: 160lm/W
- Luminaire efficiency: 125lm/W
- LED's consumption: 25,2W
- Luminaire consumption: 28,7W
- Power factor: 0,93

#### TECHNICAL SPECS 3000K - 28,7W

- LED's output: 3867lm@tc25°C
- Luminaire output: 3454lm@ta25°C
- LED's efficiency: 153,5lm/W
- Luminaire efficiency: 120lm/W

- LED's consumption: 25,2W
- Luminaire consumption: 28,7W
- Power factor: 0,93

#### TECHNICAL SPECS 4000K - 56,8W

- LED's output: 7406lm@tc25°C
- Luminaire output: 6614lm@ta25°C
- LED's efficiency: 146lm/W
- Luminaire efficiency: 116,3lm/W
- LED's consumption: 50,7W
- Luminaire consumption: 56,8W
- Power factor: 0,93


#### TECHNICAL SPECS 3000K - 56,8W

- LED's output: 7103lm@tc25°C
- Luminaire output: 6343lm@ta25°C
- LED's efficiency: 140lm/W
- Luminaire efficiency: 111,7lm/W
- LED's consumption: 50,7W
- Luminaire consumption: 56,8W
- Power factor: 0,93

Rev 03 - 05/04/22

#### Details

- Conformity with EU Directives
- Conforms to all regional/local laws against light pollution
- Double insulation/class II
- IK08
- RG1
- CRI>80
- IP 65



90-295V 50/60Hz 28,7W						
CE	CUT OFF	IK 08	RG1	CRI ≥80	IP65	

