

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### New Stelo TP opaled

**Code : 1053184N**

#### PRODUCT FAMILY

- Outdoor residential cylindrical shaped luminaire, suitable for upright installation on poles Ø60mm on top (IP65)

#### MATERIALS CHARACTERISTICS

- Aluminium housing EN AW 6026, manufactured with numerical control machines and then anodized
- Screw-neck diffuser in translucent PMMA (acrylic) with brushed effect, connected to the lamp-holder compartment via a black polycarbonate joint, and sealed with pure neutral silicone anti-mold with low elastic modulus for an excellent resistance to aging, weathering, and UV rays
- Power supply compartment in PC (polycarbonate) black granule
- Fixing spring in harmonic steel AISI 301
- Silicone gaskets
- A2 stainless steel screws

Mechanical properties of silicone, polymerized 7 days at 22°C and 50% relative humidity

- Hardness, Shore A 37
- Tensile strength MPa 2,5
- Elongation at break %680

#### COLOUR

- Black

#### WEIGHT

- Luminaire: 0,4kg
- Single package: 0,5kg (373x105x105mm)

#### LIGHTING CHARACTERISTICS

- LED's lighting source in fixed position
- Immediately ON at 100% of light flux
- Monochromatic LED module (12 Led's)
- Round symmetrical light throw

#### WIRING CHARACTERISTICS

- LED's module 4,3W
- Built-in driver (350mA driver output)
- PG9 plastic cable gland equipped with osmotic valve for air and humidity leakage (reducing the overpressures)
- Connection to the main supply through a H05RN-F 2x0,75sqmm pre-wired cable (35cm) out of the luminaire

#### INSTALLATION AND MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops or brackets Ø60mm with maximum thickness 3mm
- Fixing by harmonic steel springs
- Ordinary maintenance not necessary
- Extraordinary maintenance by removing the screw-neck diffuser and unscrewing the screws that secure the cone, in order to reach the wiring compartment
- The "T"-3 ways IP68 connector cannot be placed inside the pole Ø60mm

#### DIMENSIONS

- Round shaped diffuser Ø80mm once installed on the pole. Visible part Ø80x165mm
- Total height 278mm

#### TECHNICAL SPECS

- Led's consumption: 4,3W
- Luminaire consumption: 5,1W
- Power factor: 0,4C
- Step MacAdam: 3
- Lifetime Led's: L70/B50>60Kh - Tc 105°C
- Warranty: 5 years

#### TECHNICAL SPECS 4000K

- Led's output: 672lm@tc25°C
- Luminaire output: 487lm@ta25°C
- Led's efficiency: 157,4lm/W
- Luminaire efficiency: 96,2lm/W


#### TECHNICAL SPECS 3000K

- Led's output: 633lm@tc25°C
- Luminaire output: 459lm@ta25°C
- Led's efficiency: 148,2lm/W
- Luminaire efficiency: 90,6lm/W

Rev 02-16/02/2023

#### Details

- Conformity with EU Directives
- Double insulation/class II
- IK02
- IP 65



100-240V 50/60Hz 5,1W

CE

□

IK02

IP65

