

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l. The company reserves the right to change models, dimensions and materials at any time without notice.

PRODUCT DATA SHEET

Luna

Code : 1032182J

PRODUCT FAMILY

Outdoor residential luminaire suitable for upright installation on poles Ø60mm on top (IP65).

MATERIAL CHARACTERISTICS

- PC (polycarbonate) housing and top cover, in black, grey metallic RAL 9006, rust, anthracite RAL7016, coloured granule.
- Screw-neck diffuser in translucent PMMA (acrylic) with brushed effect, connected to the lamp-holder compartment via a black PC (polycarbonate) joint, and sealed with pure neutral silicone anti-mold with low elastic modulus for an excellent resistance to aging, weathering, and UV rays.
- Fixing spring in harmonic steel AISI 301.
- Silicone gasket.
- A2 stainless steel screws.

Mechanical properties of silicone, polymerized 7 days at 22°C and 50% relative humidity:

- Hardness, Shore A37.
- Tensile strength MPa 2,5.
- Elongation at break %680.

COLOUR

- Black.
- Rust.
- Grey metallic RAL 9006.
- Anthracite RAL 7016.

LIGHTING CHARACTERISTICS

- Light source in fixed position.
- Immediately ON at 100% of the light flux.
- Monochromatic LED module (35 LED's)
- Round symmetrical light throw.

E27 WIRING CHARACTERISTICS

- Lamp connection E27 for led lamp 10W max., tension 250V.
- Max. lamp size allowed: Ø60xL110 mm.
- Equipped with PG9 plastic cable gland with osmotic valve for air leakage (because it limits overpressure), and humidity.
- Connection to the mains via cable H05RN-F 2x0,75 sq.mm. (35cm included).

LED'S WIRING CHARACTERISTICS

- 6,9W LED's module with built-in driver.
- 350mA driver output.
- Equipped with PG9 plastic cable gland with osmotic valve for air leakage (because it limits overpressure), and humidity.
- Connection to the mains via cable H05RN-F 2x0,75 sq.mm. (35cm included).

INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Luminaire for direct installation on pole tops or brackets Ø60mm with maximum thickness 3mm.
- Fixing by expansion spring made of harmonic steel.
- Ordinary maintenance to be conducted by untightening the diffuser with screw neck.
- Ordinary and extraordinary maintenance on LED's wiring is not necessary.

DIMENSIONS

- Diffuser with round section Ø170 mm.
- Ø240x121 mm.

GENERAL SPECS

- LED's module consumption: 6,9W

- Luminaire consumption: 8,7W
- Power factor: 0,6C
- Step MacAdam: 3
- Led Lifetime: L70/B50>60kh – Tc 105°C
- 5-year warranty

TECHNICAL SPECS 4000K

- LED's module output: 1302lm@tc25°C
- Luminaire output : 774lm@tc25°C
- LED's module efficiency: 119lm@tc25°C
- Luminaire efficiency: 108lm@tc25°C


TECHNICAL SPECS 3000K


- LED's module output: 1219lm@tc25°C
- Luminaire output : 696lm@tc25°C
- LED's module efficiency: 111lm@tc25°C
- Luminaire efficiency: 101lm@tc25°C

Rev 02-27/02/2023

Details

- Conformity with EU Directives
- Double insulation/class II
- IK03
- IP 65



220-240V 50/60Hz 8,7W LED			
CE		IK 03	IP65

