

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Versus Up-Down

**Code : 1012178J**

#### PRODUCT FAMILY

-Outdoor residential luminaire for direct wall installation (IP65).

#### MATERIAL CHARACTERISTICS

- PC (polycarbonate) housing in black granule, or painted in rust, grey metallic RAL 9006, grey anthracite RAL 7016 textured, white.
- Flush body diffuser in translucent PMMA (acrylic) with acid-etched effect.
- Polyester powder coating with a pre-treatment for outdoor (Phosphochrome) to ensure high protection against weathering.
- Silicone gaskets.
- A2 stainless steel screws.

#### COLOUR

- Black.
- Grey anthracite RAL 7016 textured.
- Rust.
- Grey metallic RAL 9006.
- White.

#### LIGHTING CHARACTERISTICS (LED VERSION)

- Light source in fixed position UP/DOWN.

#### WIRING CHARACTERISTICS

- Lamp connection R7S led – max 14W max 250V.
- Max. lamp length 118mm.

#### INSTALLATION AND ORDINARY MAINTENANCE CHARACTERISTICS

- Direct wall installation luminaire through n. 2 screws (not included).
- Ordinary maintenance to be conducted by unscrewing the fixing dowels on the sides, and removing the diffuser and frame.
- Power supply cables entry via a grommet.

#### DIMENSIONS

- 122x230x150mm.


#### GENERAL SPECS

- 5-year warranty.

Rev 02-14/03/2023

#### Details

- CLASS I
- IK06
- IP 65



14W R7s



IK  
06

IP65