

This document is exclusive MARECO LUCE s.r.l., is strictly prohibited disclosure or reproduction, even partial, as well the use of without written consent of MARECO LUCE s.r.l..The company reserves the right to change models, dimensions and materials at any time without notice.

## PRODUCT DATA SHEET

### Pin 260

#### Code : 0765188B

##### PRODUCT FAMILY

- Led round surface applique for direct wall and ceiling mounting, 3000K/4000K selectable via a CCT switch, suitable for indoor and outdoor (IP65).

##### MATERIAL CHARACTERISTICS

- Base in ABS coloured granule.
- Ring in polycarbonate coloured granule.
- Diffuser in polycarbonate UV stabilised, opal brushed.
- A2 stainless steel screws

##### COLOUR

- White.
- Dove grey.
- Anthracite.

##### LIGHTING CHARACTERISTICS

- 3000K/4000K led module, selectable colour temperature via a CCT switch.
- Led lighting source in fixed position.
- Round symmetrical light throw.
- Immediately ON at 100% of light flux.

##### WIRING CHARACTERISTICS

- Supply tension: 220-240V 50/60Hz.
- 11W led module (65Led's 3000K + 65Led's 4000K).
- Built-in flicker free driver.

##### INSTALLATION CHARACTERISTICS

- Direct installation on wall or ceiling through dowels (not included).
- Power supply cable entry with rear grommet for both single wires and sheathed cable.
- CCT setting by dip-switches to be reached out by turning the polycarbonate ring anti-clock wise.
- Tool-free removable led's circuit board, secured with a hinge and a blocking lever.


##### DIMENSIONS

- Ø260x73mm


##### TECHNICAL FEATURES

- CCT switch 3000/4000K
- Led circuit board consumption: 11W
- Luminaire consumption: 13W
- Luminaire output (3000K) : 1000lm@ta25°C
- Luminaire output (4000K) : 1100lm@ta25°C
- Luminaire efficiency (3000K) : 76.9lm/W@ta25°C
- Luminaire efficiency (4000K) : 84.6lm/W@ta25°C
- Power factor: >0.9
- Led life time: L70=20kh
- Driver life time: 30Kh
- Step MacAdam: 6
- RG1
- 5-year warranty

- RG1
- CRI>80
- IP 65



220-240V 50/60Hz 13W LED					
CE	□	IK 08	RG1	CRI ≥ 80	IP65



Rev. 0 - 19/09/23

##### Details

- Conformity with EU Directives
- Double insulation/class II
- IK08